



ATMOR MP MODEL

Electric Instantaneous Water Heater

The **ATMOR In-line or Multi-Point** instantaneous water heater is the "aesthetic solution". Installed below the eye level and completely hidden. The in-line water heater connected to the water supply before the valve (no need for extra accessories). This especially made water heater is designed to supply hot water for the whole bathroom or more than one point-of-use.

STANDARD FEATURES:

- Fully automatic operation
- Auto Shut-off (at 55°C)
- Equipped with Pressure Relief Valve (PRV)
- User friendly buttons and switches
- High Grade Composite Materials
- Internationally approved aesthetic and engineering design

TECHNICAL SPECIFICATION

MODEL	ATMOR Multipoint Model		
TECHNOLOGY/STANDARD	GERMAN STANDARD TECHNOLOGY		
TYPE	Electric Instantaneous (demand) Water Heater		
OPERATION	Fully Automatic		
ACTIVATING MECHANISM	Flow Sensor Activated Relay		
TEMPERATURE SELECTION	Three-way temperature selection		
SAFETY	Auto-thermal cut-off at 52°C to 55°C; final cut-off at 80°C ± 10%		
MATERIALS	High Grade Composite Materials		
APPLICATION	In-line; closed vented		
VOLTAGE	220 - 240 VAC		
POWER RATING	5.5 Kilowatts	8.0 Kilowatts	
CYCLES	50 Hz - 60 Hz		
PHASE	Single Phase		
POWER/HEAT SETTING	Low: 2.0 Kw	Med: 3.5 Kw	High: 5.5 Kw
KILOWATT LOADING	220 VAC; 5.5 Kw	230 VAC; 6.0 Kw	240 VAC; 6.6 Kw
RECOMMENDED CABLE SIZE	4/6 sq. mm for 5.5 Kw model		6/10 sq. mm for 8.0 Kw model
RECOMMENDED CIRCUIT BREAKER RATING	30 Amperes		40 Amperes
CABLE ENTRY	Top Right and Top left		
HEIGHT	190 mm		
WIDTH	300 mm		
DEPTH	110 mm		
INLET/OUTLET CONNECTION	15 mm (1/2 compression inlet connection)		
FLOW RATE	4 Liters / Minutes (1.05 Gallons / Minutes) @ 20°C Temp Rise		
MINIMUM ACTIVATING PRESSURE	2.5 PSI (Pounds per Square Inch)		
OPERATING WATER PRESSURE	0.3 - 7 BAR (5-100 PSI)		
ACCESSORIES	Inlet/Outlet Connection Fittings		
MANUFACTURER	ATMOR Industries		
MADE	ISRAEL		
STANDARD/CERTIFICATION	ISO 9002, CE, BEAB, TUV, UL Listed		